



TRES COMERCIAL, S.L.

C/ Penedés, 16-26 | Zona industrial, Sector A | 08759 Vallirana (Barcelona)

93 683 40 04 | comercial@tresgriferia.com

www.tresgriferia.com

Certificate No.:	CC19016905OM2022
Initial Certification:	13/05/2022
Issue Date:	01/01/2024
Expiry Date:	01/01/2029

CERTIFICATE OF CONFORMITY

TRES COMERCIAL S.L., with registered office at C/ Penedès 16-26, Zona Industrial - Sector A, 08759 Vallirana (Barcelona), hereby declares under its sole responsibility that the sanitary tapware:

Brand: TRES
Model(s): 19016905OM
Collection: OVER-WALL
Family: Thermostatic

As the subject of this declaration, is produced under a quality management system in accordance with the UNE-EN ISO 9001:2015 standard (ER-1111/1999) for the production and assembly of sanitary tapware and accessories, and complies with the requirements of both national and European standards:

Royal Decree 145/2023 of 28 February (industrial safety) Annex 1: 6. Sanitary tapware.

Royal Decree 3/2023 of 10 January regarding technical and sanitary criteria for drinking water quality, control, and supply.

EN-1111: Sanitary Tapware. Thermostatic mixers (PN 10). General technical specifications.

EN 248: Corrosion resistance and adhesion of surface coating.

Characteristics and performance in the attached technical sheet.

Quality Department

 TRES COMERCIAL SL

190169050M

OVER-WALL

2-way Over-wall thermostatic wall tap with shower bar connection

- To complete with the rest of the shower parts.
- Inverter integrated into the flow regulator.
- Square-round handle.



24K Matt Gold Finish



Environmental Quality Guarantee (Catalonia)



Distributor cartridge: 29928302



Easy-Clean®. The thermostatic cartridge is easy to clean without losing temperature calibration



Connecting element: MURAL G1/2"



Tres Instant: The thermostatic cartridge ensures a constant flow of water at the desired temperature, in spite of pressure or temperature changes.



Material: Low lead content brass



New



Corrosion resistance



Tres Touch-cool®. The tap surface remains at a temperature suitable for touching, thus preventing burns.

