


Submitted Model No.: _____

Specific Features: _____



▲ Designate proper finish suffix

Spray Patterns



Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.deltafaucet.com for finish options and product availability.



see what Delta can do™

SHOWER HEAD

- 5-Spray Setting Shower Head
- Push Button Diverter

FEATURES:

- H₂Okinetic Technology[®] Shower Head
- Touch-Clean[®] Nozzles

STANDARD SPECIFICATIONS

- Maximum 1.75 gpm @ 80 psi, 6.6 L/min @ 550 kPa
- ABS shower head with five spray settings, pause is a non-positive shut-off
- Change spray modes with push button
- Self connector swivel angle is 32° (16° per side)
- Standard 1/2"-14 NPT pipe fitting

WARRANTY

- Parts and Finish - Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date of purchase.
- Electronic Parts and Batteries (if applicable) - 5 years from the date of purchase; or for commercial purchasers, 1 year from the date of purchase. No warranty is provided on batteries.



COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- EPA WaterSense[®]

Delta Faucet Company

55 E. 111th Street, Indianapolis, IN 46280
 350 South Edgeware Road, St. Thomas, ON N5P 4L1
 © 2018 Delta Faucet Company