

# LAUFEN INSTALLATION SYSTEM

**CU1**

**Concealed frame for urinal without integrated control**

**89266.3**



## TECHNICAL DATA

Order no.	89266.3
matching for	Urinal TAMARO, order no. 84009.0, TARO-NOVA, order no. 84000.0
Specifications	Self-supporting steel frame for drywall and solid building, for surface and flush installation, pre-assembled with concealed kit LAUFEN SmartControl-U. Connections pre-set to fit TAMARO 84009.0
Other specifications	Galvanized leg supports, rotatable, height-adjustable 0-200 mm. Capable to resist 100 kg
Water connection	right Rp 1/2", brass
Flow pressure range	1-8 bar
Installation depth	140-195 mm
Weight	13,3 kg

Mounting acc. incl.	Shut-off valve, building protection with cover, M8 threaded rod and fastening material.
Mounting acc. excl.	Horizontal inlet connection 1/2", order no. 89900.5 Sound insulation set, order no. 89269.6
Accessories excl.	Front plate with infrared control, mains version with Bluetooth, order no. 370660.004.720.1 battery version 6V, order no. 370660.004.721.1
Mounting information	Please note the necessary wall thickness of 80 mm in case of pre-wall installation. System installation is also possible between modular walls (plaster-board).
Colours	Surface powder coated blue

## TECHNICAL DRAWINGS / S 1 : 20

