

# LAUFEN INSTALLATION SYSTEM

## CU3

### Concealed frame for urinal with integrated control and for waterless urinal

89266.5



#### TECHNICAL DATA

Order no.	89266.5	Other specifications	Galvanized leg supports, rotatable, height-adjustable 0-200 mm. Capable to resist 100 kg
matching for	Urinal with integrated control ANTERO, order no. 84015.4, 84015.5, 84015.6, 84015.9, 84115.0, 84115.2 CAPRINO PLUS, order no. 84206.5, 84206.6 LEMA, order no. 84019.4, 84019.6, 84019.9, 84119.0, 84119.2 TAMARO-S90, order no. 84010.3, 84010.4, TAMARO-VS NEW, order no. 84112.2, 84112.3, VAL order no. 84028.4, 84028.6 Waterless urinal LEMA order no. 84319.5, 84319.7	Water connection	R 1/2", brass, matching for standard pipe systems
Specifications	Self-supporting steel frame for drywall and solid building, for surface and flush installation. Connections pre-set to fit LEMA 84019.4, 84019.6, 84019.9	Flow pressure range	1-8 bar
		Installation depth	140-195 mm
		Weight	11,5 kg
		Mounting acc. incl.	Building protection with cover, M8 threaded rod and fastening material.
		Mounting acc. excl.	Sound insulation set, order no. 89269.6
		Mounting information	Please note the necessary wall thickness of 80 mm in case of pre-wall installation. System installation is also possible between modular walls (plaster-board).
		Colours	Surface powder coated blue

#### TECHNICAL DRAWINGS / S 1 : 20

