

LAUFEN INSTALLATION SYSTEM

TW2

Concealed cistern for floorstanding WC pan 89466.4



TECHNICAL DATA

Order no.	89466.4	Mounting acc. incl.	Fastening set for the wall, WC connection set, tiling set, protection cap (for flush pipe connector) and angle valve 1/2".
Certified to	EN 14055	Accessories excl.	Actuator plates dual flush, order no. 89566.1, 89566.2 (stainless steel) Electronic actuator plate dual flush, order no. 89566.3, 89566.4
matching for	All LAUFEN floorstanding WC pans	Mounting information	Please note the necessary wall thickness of 80 mm in case of pre-wall installation. Height from finished floor to top of WC pre-set to 400 mm, adjustable between 390-450 mm. Height dimension from finished floor to feeding elbow of the toilet flange. System installation is also possible between modular walls (plasterboard).
Specifications	For mounting in front of a solid or drywall construction, concealed installation, with frontal actuator, with water condensation insulation. Dual-Flush 6/3-1 (4/2-1-flush). Flush valve with silicon seal. Fill valve with anti-siphon system.	Colours	White
Water inlet	top or rear R 1/2", brass		
Flow pressure range	0.5-10 bar		
Water temperature	max. 25°C		
Tank	Thickness 110 mm, material PP		
Installation depth	125 mm		
Weight	3,8 kg		

TECHNICAL DRAWINGS / S 1 : 20

